Bayled TPU90150

IP65 & IK10 Rated
Tri-select Highbay

Made For Trade

Highbay manufactured with a robust integrated aluminium heatsink and precision-engineered cooling fins for optimal heat dissipation, ensuring longevity and efficiency. Equipped with a heavy-duty loop and hook for secure mounting, it also offers additional mounting options upon request, providing versatility to suit various installation needs.

Featuring tri-select technology, allowing users to switch between three wattage options (90W, 120W, 150W), three beam angles (60°, 90°, 120°) and three CCT options (3000K, 4000K, 5000K) offering the ultimate versatility for high bay applications. Supplied with an integral flicker free IP65 rated driver.

Product	CCT	Trim Colour	Driver	Order Codes
TPU90150	Tri-colour	Black Trim	Non-dim	TPU90150-TRI-B-ND

Specifications	
Trim Colour Options	Black
Dimensions	Ø280 x 142 (H) mm
Weight	1653 g
LED Power	90W, 120W, 150W
LED Type	SMD
Lumen Output	12500 lm, 17400 lm, 21000 lm
Efficacy	139 lm/W, 145 lm/W, 140 lm/W
CCT Technology	Switchable CCT
Colour Temperature	3000K, 4000K, 5000K
Colour Rendering	CRI 80+
Lifetime	50,000 hours
Beam Angle	Adjustable 60°, 90°, 120°
System Power	93.4W, 122.3W, 151.8W Typical
Input	220-240V AC 50/60 Hz
Power Factor	>0.90
Dimming	Non-dimmable
Driver Type	Integral, Flicker Free
Connection Type	2 m, Flex and Plug
Ingress Protection	IP65
Impact Resistance	IK10
Warranty	3 Years
Accessories	Aluminium Reflector | Prismatic Reflector





CCT TRI | ADJ° | CRI 80+ | IP65 | IK10

trendfortrade.com.au

Trend For Trade. Made For Trade.

powered by TREND

Bayled TPU90150

IP65 & IK10 Rated
Tri-select Highbay

Made For Trade

Highbay manufactured with a robust integrated aluminium heatsink and precision-engineered cooling fins for optimal heat dissipation, ensuring longevity and efficiency. Equipped with a heavy-duty loop and hook for secure mounting, it also offers additional mounting options upon request, providing versatility to suit various installation needs.

Featuring tri-select technology, allowing users to switch between three wattage options (90W, 120W, 150W), three beam angles (60°, 90°, 120°) and three CCT options (3000K, 4000K, 5000K) offering the ultimate versatility for high bay applications. Supplied with an integral flicker free IP65 rated driver.

Accessories

AR-B
Aluminium Reflector, Black

AR-S
Aluminium Reflector, Silver

PR
Prismatic Reflector

trendfortrade.com.au

Trend For Trade. Made For Trade.

powered by TREND